


# EMBOUIT "S" : ORFS

## F40S

coudé à 45°

NORMES : ISO 8434-3  
SAE J516/J1453

FILETAGE : UNF  
ASME B1.1



| D.N. |       | Référence |                  | Filetage   | Dimensions (mm) |          |       |       |      |
|------|-------|-----------|------------------|------------|-----------------|----------|-------|-------|------|
| mm   | "     | Code      | Désignation      | F          | C               | Ø inter. | L     | A     | B    |
| 6    | 1/4"  | 1570614   | S06 F40S 9/16    | 9/16"-18   | 17              | 4,0      | 73,0  | 47,0  | 12,0 |
| 10   | 3/8"  | 1571017   | S10 F40S 11/16   | 11/16"-16  | 22              | 7,0      | 84,0  | 54,0  | 14,0 |
| 12   | 1/2"  | 1571221   | S12 F40S 13/16   | 13/16"-16  | 24              | 9,5      | 93,0  | 61,0  | 17,0 |
| 16   | 5/8"  | 1571625   | S16 F40S 1"      | 1"-14      | 30              | 12,0     | 111,0 | 71,0  | 20,0 |
| 20   | 3/4"  | 1572030   | S20 F40S 1"3/16  | 1"3/16-12  | 36              | 14,5     | 122,0 | 78,0  | 21,0 |
| 25   | 1"    | 1572537   | S25 F40S 1"7/16  | 1"7/16-12  | 41              | 21,0     | 162,0 | 108,0 | 29,0 |
| 32   | 1"1/4 | 1573243   | S32 F40S 1"11/16 | 1"11/16-12 | 50              | 26,5     | 187,0 | 129,0 | 32,0 |
| 40   | 1"1/2 | ◆         | S40 F40S 2"      | 2"-12      | 60              | 32,0     | 215,0 | 151,0 | 35,0 |


Notes

## F90S

coudé à 90°

NORMES : ISO 8434-3  
SAE J516/J1453

FILETAGE : UNF  
ASME B1.1



| D.N. |       | Référence |                  | Filetage   | Dimensions (mm) |          |       |       |      |
|------|-------|-----------|------------------|------------|-----------------|----------|-------|-------|------|
| mm   | "     | Code      | Désignation      | F          | C               | Ø inter. | L     | A     | B    |
| 6    | 1/4"  | 1580614   | S06 F90S 9/16    | 9/16"-18   | 17              | 4,0      | 59,0  | 33,0  | 24,0 |
| 10   | 3/8"  | 1581017   | S10 F90S 11/16   | 11/16"-16  | 22              | 7,0      | 68,0  | 38,0  | 29,0 |
| 12   | 1/2"  | 1581221   | S12 F90S 13/16   | 13/16"-16  | 24              | 9,5      | 72,0  | 40,0  | 36,0 |
| 16   | 5/8"  | 1581625   | S16 F90S 1"      | 1"-14      | 30              | 12,0     | 86,0  | 46,0  | 45,0 |
| 20   | 3/4"  | 1582030   | S20 F90S 1"3/16  | 1"3/16-12  | 36              | 14,5     | 96,0  | 52,0  | 50,0 |
| 25   | 1"    | 1582537   | S25 F90S 1"7/16  | 1"7/16-12  | 41              | 21,0     | 126,0 | 72,0  | 63,0 |
| 32   | 1"1/4 | 1583243   | S32 F90S 1"11/16 | 1"11/16-12 | 50              | 26,5     | 146,0 | 88,0  | 73,0 |
| 40   | 1"1/2 | ◆         | S40 F90S 2"      | 2"-12      | 60              | 32,0     | 169,0 | 105,0 | 98,0 |

Notes

En fonction des évolutions techniques, les données peuvent être modifiées sans préavis - Photo non contractuelle - Les normes sont citées à titre indicatif.

