


INTERLOCK "V" : MÉTRIC 24° "S"

F4EO_S coudé à 45°

NORMES : ISO 8434-1
DIN 3865S

FILETAGE : ISO 68
ISO 261




D.N.		Référence		Filetage		Dimensions (mm)				
mm	"	Code	Désignation	T	F	C	Ø inter.	L	A	B
20	3/4"	◆	V20 F4EO 20S	20S	M30 x 2.0	36	14,5	140,0	78,0	25,0
20	3/4"	3212025	V20 F4EO 25S	25S	M36 x 2.0	46	14,5	142,0	80,0	28,0
25	1"	◆	V25 F4EO 25S	25S	M36 x 2.0	46	21,0	178,0	106,0	31,0
25	1"	3212530	V25 F4EO 30S	30S	M42 x 2.0	50	21,0	181,0	109,0	33,0
32	1"1/4	3213238	V32 F4EO 38S	38S	M52 x 2.0	60	26,5	227,0	140,0	36,0

Notes

F9EO_S coudé à 90°

NORMES : ISO 8434-1
DIN 3865S

FILETAGE : ISO 68
ISO 261



D.N.		Référence		Filetage		Dimensions (mm)				
mm	"	Code	Désignation	T	F	C	Ø inter.	L	A	B
20	3/4"	◆	V20 F9EO 20S	20S	M30 x 2.0	36	14,5	110,0	48,0	51,0
20	3/4"	3222025	V20 F9EO 25S	25S	M36 x 2.0	46	14,5	110,0	48,0	55,0
25	1"	◆	V25 F9EO 25S	25S	M36 x 2.0	46	21,0	140,0	68,0	66,0
25	1"	3222530	V25 F9EO 30S	30S	M42 x 2.0	50	21,0	140,0	68,0	70,0
32	1"1/4	3223238	V32 F9EO 38S	38S	M52 x 2.0	60	26,5	182,0	95,0	79,0

Notes

En fonction des évolutions techniques, les données peuvent être modifiées sans préavis - Photo non contractuelle - Les normes sont citées à titre indicatif.

