


INTERLOCK "V" : BSP 60°

FB_(FBO)



NORMES : BS 5200/86
NCB174

FILETAGE : BSPP
ISO 228



D.N.		Référence		Filetage	Dimensions (mm)			
mm	"	Code	Désignation	F	C	Ø inter.	L	A
20	3/4"	◆	V20 FBO 3/4"	3/4"	32	14,5	85,2	23,2
20	3/4"	◆	V20 FBO 1"	1"	41	14,5	90,0	28,0
25	1"	3402534	V25 FBO 1"	1"	38	21,0	95,8	23,8
25	1"	◆	V25 FBO 1"1/4	1"1/4	50	21,0	110,0	38,0
32	1"1/4	3403242	V32 FBO 1"1/4	1"1/4	50	26,5	116,3	29,3
32	1"1/4	◆	V32 FBO 1"1/2	1"1/2	55	26,5	121,0	34,0
40	1"1/2	3404049	V40 FBO 1"1/2	1"1/2	55	32,0	121,0	29,0
50	2"	3405060	V50 FBO 2"	2"	70	44,0	126,0	29,0


Notes

MB_(MBG)



NORMES : BS 5200/86

FILETAGE : BSPP
ISO 228



D.N.		Référence		Filetage	Dimensions (mm)			
mm	"	Code	Désignation	F	C	Ø inter.	L	A
20	3/4"	◆	V20 MB 3/4"	3/4"	32	14,5	93,9	31,9
20	3/4"	◆	V20 MB 1"	1"	41	14,5	99,0	37,0
25	1"	3442534	V25 MB 1"	1"	41	21,0	110,4	38,4
25	1"	◆	V25 MB 1"1/4	1"1/4	50	21,0	114,6	42,6
32	1"1/4	3443242	V32 MB 1"1/4	1"1/4	50	26,5	129,0	42,0
32	1"1/4	◆	V32 MB 1"1/2	1"1/2	55	26,5	131,0	44,0
40	1"1/2	3444049	V40 MB 1"1/2	1"1/2	55	32,0	137,5	45,5
50	2"	3445060	V50 MB 2"	2"	70	44,0	150,0	53,0

Notes

En fonction des évolutions techniques, les données peuvent être modifiées sans préavis - Photo non contractuelle - Les normes sont citées à titre indicatif.

