


# INTERLOCK "V" : NPT (BRIGGS 60°)

## MN\_(NPTF)

NORMES : SAE J516/J514  
J476/ASA B2-1

FILETAGE : NPT/NPSM  
ANSI/ASME B1.20.1




D.N.		Référence		Filetage	Dimensions (mm)			
mm	"	Code	Désignation	F	C	Ø inter.	L	A
20	3/4"	◆	V20 MN 3/4	3/4" NPT	27	14,5	96,1	34,1
20	3/4"	◆	V20 MN 1"	1" NPT	36	14,5	102,0	40,0
25	1"	3612534	V25 MN 1"	1" NPT	36	21,0	113,0	41,0
25	1"	3612542	V25 MN 1"1/4	1"1/4 NPT	46	21,0	116,0	44,0
32	1"1/4	3613242	V32 MN 1"1/4	1"1/4 NPT	46	26,5	133,6	46,6
32	1"1/4	3613249	V32 MN 1"1/2	1"1/2 NPT	40	26,5	135,0	48,0
40	1"1/2	3614049	V40 MN 1"1/2	1"1/2 NPT	50	32,0	139,9	47,9
40	1"1/2	3614060	V40 MN 2"	2" NPT	65	32,0	145,0	53,0
50	2"	3615060	V50 MN 2"	2" NPT	65	44,0	151,2	54,2

Notes

# INTERLOCK "V" : COLLET 6000 PSI

## CS

NORMES : SAE J516-code 62  
J518



D.N.		Référence		Dimensions (mm)			
mm	"	Code	Désignation	D1	Ø inter.	L	A
20	3/4"	3752027	V20 CS 3/4	41,3	14,5	119,5	57,5
20	1"	◆	V20 CS 1"	47,6	14,5	122,1	60,1
25	1"	3752527	V25 CS 3/4	41,3	21,0	131,0	59,0
25	1"	3752534	V25 CS 1"	47,6	21,0	135,8	63,8
25	1"	3752542	V25 CS 1"1/4	54,0	21,0	139,8	67,8
32	1"1/4	3753242	V32 CS 1"1/4	54,0	26,5	156,1	69,1
32	1"1/4	3753249	V32 CS 1"1/2	63,5	26,5	165,6	78,6
40	1"1/2	3754049	V40 CS 1"1/2	63,5	32,0	170,4	78,4
50	2"	3755060	V50 CS 2"	79,4	44,0	196,1	99,1

Notes