


EMBOUIT "S" : ORFS

FOS

NORMES : ISO 8434-3
SAE J516/J1453

FILETAGE : UNF
ASME B1.1




D.N.		Référence		Filetage	Dimensions (mm)			
mm	"	Code	Désignation	F	C	Ø inter.	L	A
6	1/4"	1560614	S06 FOS 9/16	9/16"-18	17	4,0	46,5	20,5
8	5/16"	◆	S08 FOS 11/16	11/16"-16	22	5,5	47,9	21,9
10	3/8"	1561017	S10 FOS 11/16	11/16"-16	22	7,0	52,0	22,0
12	1/2"	1561221	S12 FOS 13/16	13/16"-16	24	9,5	57,6	25,6
12	1/2"	1561225	S12 FOS 1"	1"-14	30	9,5	61,9	29,9
16	5/8"	1561625	S16 FOS 1"	1"-14	30	12,0	61,9	29,9
20	3/4"	1562030	S20 FOS 1"3/16	1"3/16-12	36	14,5	77,0	33,0
25	1"	1562537	S25 FOS 1"7/16	1"7/16-12	41	21,0	88,1	34,1
32	1"1/4	1563243	S32 FOS 1"11/16	1"11/16-12	50	26,5	93,5	35,5
40	1"1/2	◆	S40 FOS 2"	2"-12	60	32,0	101,0	37,0

Notes

FOSH

NORMES : ISO 8434-3
SAE J516/J1453

FILETAGE : UNF
ASME B1.1



D.N.		Référence		Filetage	Dimensions (mm)				
mm	"	Code	Désignation	F	C	C1	Ø inter.	L	A
6	1/4"	1530614	S06 FOSH 9/16	9/16"-18	19	14	4,0	54,0	28,0
6	1/4"	1530617	S06 FOSH 11/16	11/16"-16	22	17	4,0	56,8	30,8
10	3/8"	1531017	S10 FOSH 11/16	11/16"-16	22	17	7,0	62,0	32,0
10	3/8"	1531021	S10 FOSH 13/16	13/16"-16	24	19	7,0	65,3	35,3
12	1/2"	1531221	S12 FOSH 13/16	13/16"-16	24	19	9,5	65,4	33,4
12	1/2"	1531225	S12 FOSH 1"	1"-14	30	24	9,5	71,6	39,6
16	5/8"	1531625	S16 FOSH 1"	1"-14	30	24	12,0	79,6	39,6
20	3/4"	1532025	S20 FOSH 1"	1"-14	30	27	14,5	84,5	40,5
20	3/4"	1532030	S20 FOSH 1"3/16	1"3/16-12	36	27	14,5	87,0	43,0
25	1"	1532537	S25 FOSH 1"7/16	1"7/16-12	41	36	21,0	100,1	46,1
32	1"1/4	1533243	S32 FOSH 1"11/16	1"11/16-12	50	41	26,5	106,0	48,0
40	1"1/2	◆	S40 FOSH 2"	2"-12	60	50	32,0	114,6	50,6

Notes

En fonction des évolutions techniques, les données peuvent être modifiées sans préavis - Photo non contractuelle - Les normes sont citées à titre indicatif.