


# EMBOUT "S" : BSP 60°

## F9B

coudé à 90°

NORMES : BS 5200/86  
(NCB174)

FILETAGE : BSPP  
ISO 228



Notes

D.N.		Référence		Filetage	Dimensions (mm)				
mm	"	Code	Désignation	F	C	Ø inter.	L	A	B
6	1/4"	1420610	S06 F9B 1/8	1/8" -28	14	4,0	52,0	23,0	26,0
6	1/4"	1420613	S06 F9B 1/4	1/4" -19	19	4,0	55,0	23,0	29,0
6	1/4"	1420617	S06 F9B 3/8	3/8" -19	22	4,0	59,0	23,0	33,0
8	5/16"	1420813	S08 F9B 1/4	1/4" -19	19	5,5	52,0	33,0	32,0
8	5/16"	1420817	S08 F9B 3/8	3/8" -19	22	5,5	60,0	33,0	34,0
10	3/8"	1421017	S10 F9B 3/8	3/8" -19	22	7,0	66,0	35,0	36,0
10	3/8"	1421021	S10 F9B 1/2	1/2" -14	27	7,0	70,0	35,0	40,0
12	1/2"	1421221	S12 F9B 1/2	1/2" -14	27	9,5	76,0	39,0	44,0
12	1/2"	1421223	S12 F9B 5/8	5/8" -14	30	9,5	71,0	39,0	47,0
12	1/2"	1421227	S12 F9B 3/4	3/4" -14	32	9,5	78,0	39,0	49,0
16	5/8"	1421621	S16 F9B 1/2	1/2" -14	27	12,0	86,0	48,0	47,0
16	5/8"	1421623	S16 F9B 5/8	5/8" -14	30	12,0	90,0	48,0	50,0
16	5/8"	1421627	S16 F9B 3/4	3/4" -14	32	12,0	86,0	48,0	52,0
20	3/4"	1422027	S20 F9B 3/4	3/4" -14	32	14,5	96,0	50,0	52,0
20	3/4"	1422034	S20 F9B 1"	1" -11	41	14,5	97,0	50,0	56,0
25	1"	1422534	S25 F9B 1"	1" -11	41	21,0	121,0	72,0	67,0
32	1"1/4	1423242	S32 F9B 1"1/4	1"1/4 -11	50	26,5	131,5	73,5	88,0
40	1"1/2	1424049	S40 F9B 1"1/2	1"1/2 -11	55	32,0	151,0	87,0	100,0
50	2"	1425060	S50 F9B 2"	2" -11	70	44,0	174,5	102,5	112,0