


EMBOUT "S" : KOMATSU

FK

NORMES : JIS B 8363
(JIS B 0207)

FILETAGE : ISO 228



D.N.		Référence		Filetage	Dimensions (mm)				
mm	"	Code	Désignation	F	C	C1	Ø inter.	L	A
6	1/4"	1490614	S06 FK 14	M14 x 1.5	19	17	4,0	47,5	21,5
8	5/16"	1490816	S08 FK 16	M16 x 1.5	22	17	5,5	48,0	22,0
10	3/8"	1491014	S10 FK 14	M14 x 1.5	19	17	7,0	51,5	21,5
10	3/8"	1491018	S10 FK 18	M18 x 1.5	24	19	7,0	52,5	22,5
12	1/2"	1491222	S12 FK 22	M22 x 1.5	27	22	9,5	58,0	26,0
16	5/8"	1491624	S16 FK 24	M24 x 1.5	32	27	12,0	100,0	60,0
20	3/4"	1492030	S20 FK 30	M30 x 1.5	36	32	14,5	77,5	33,5
25	1"	1492533	S25 FK 33	M33 x 1.5	41	36	21,0	90,0	36,0
32	1"1/4	♦	S32 FK 36	M36 x 1.5	46	41	26,5	98,0	40,0
40	1"1/2	♦	S40 FK 42	M42 x 1.5	50	46	32,0	106,5	42,5


Notes
JIS inversé 60°

EMBOUT "S" : TOYOTA

FT

NORMES : JIS B 8363
(JIS B 0202)

FILETAGE : BSPP



D.N.		Référence		Filetage	Dimensions (mm)				
mm	"	Code	Désignation	F	C	C1	Ø inter.	L	A
6	1/4"	♦	S06 FT 1/4	1/4"-19	19	17	4,0	47,5	21,5
10	3/8"	1481017	S10 FT 3/8	3/8"-19	22	19	7,0	52,5	22,5
12	1/2"	1481221	S12 FT 1/2	1/2"-14	27	22	9,5	58,0	26,0
20	3/4"	♦	S20 FT 3/4	3/4"-14	32	27	14,5	75,0	31,0
25	1"	♦	S25 FT 1"	1"-11	41	36	21,0	90,0	36,0
32	1"1/4	♦	S32 FT 1"1/4	1"1/4-11	50	46,0	26,5	98,5	40,5
40	1"1/2	♦	S40 FT1"1/2	1"1/2-11	55	50,0	32,0	106,5	42,5

Notes